

# MATERIAL SAFETY DATA SHEET

## FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by US Department of Labor Essentially Similar to Form OSHA 20)

Date Issued 05/17/05

---

### SECTION I

---

#### MANUFACTURERS NAME

AZ-TEC COATINGS, INC.

#### STREET ADDRESS

6351 S. TUCSON BLVD.

#### CITY, STATE, AND ZIP CODE

TUCSON, AZ 85706

#### EMERGENCY TELEPHONE NUMBER

1-888-899-7663

#### MANUFACTURER'S CODE IDENTIFICATION

#### PRODUCT CLASS

SNOW-COAT Roof Coating

ELASTOMERIC ROOF COATING (PIGMENTED)

#### TRADE NAME

**SNOW-COAT**

---

### SECTION II- HAZARDOUS INGREDIENTS

---

INGREDIENT	PERCENT	TLV PPM	TLV Mg/M3	LEL	VAPOR PRESSURE
ETHYLENE GLYCOL CAS # - 107-21-1	<.5%	50			
POLYMER	>40%	*			
<b>CAS #- 9003-55-8</b>					

ADDITIONAL INFORMATION- \* NOT HAZARDOUS

#### Hazardous Materials Identification System (HMIS)

Health	Flammability	Reactivity	Personal Protection
1	0	0	G

---

### SECTION III – PHYSICAL DATA

---

BOILING RANGE: 200 °F - 215°F VAPOR DENSITY  HEAVIER  LIGHTER, THAN AIR

EVAPORATION RATE  FASTER  SLOWER,  
THAN ETHER PERCENT VOTILE BY  
VOLUME - 5 % WEIGHT PER GALLON  
BY VOLUME 11.7 LBS

---

### SECTION IV – FIRE AND EXPLOSION HAZARD DATA

---

DOT CATEGORY - NR FLASH POINT- N/A WATER BASED

EXTINGUISHING MEDIA- CO2, FOAM, & DRY CHEMICAL

UNUSUAL FIRE AND EXPLOSION HAZARDS- CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. PRODUCTS OF COMBUSTION MAY BE TOXIC

SPECIAL FIRE FIGHTING PROCEDURES- WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY BE USED TO COOL CLOSED CONTAINERS. HIGH PRESSURE STREAM WILL SPREAD FIRE.

---

### SECTION V – REACTIVITY DATA

---

STABILITY:  UNSTABLE  STABLE CONDITIONS TO AVOID: NONE

INCOMPATIBILTY (MATERIALS TO AVOID): STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS: BURNING DRIED FILM MAY PRODUCE OXIDES OF CARBON AND NITROGEN.

HAZARDOUS POLYMERIZATION:  MAY OCCUR  WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

---

### SECTION VI- HEALTH HAZARD DATA

---

EFFECTS OF OVEREXPOSURE- ACUTE: SKIN: PROLONGED REPEATED CONTACT MAY CAUSE IRRITATION. EYES: CONTACT MAY CAUSE IRRITATION, BLURRED VISION, REDNESS. INHALATION: EXCESSIVE BREATHING OF HIGH VAPOR CONCENTRATION CAN CAUSE POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. CARCINOGENICITY: NO- SYNERGISTIC MATERIALS: N/A. REPRODUCTIVE EFFECTS: ND. TERATOGENIC: NO. MUTAGENIC: NO.

EMERGENCY FIRST AID PROCEDURE-EYES: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING/ SHOES. WASH Affected AREAS WITH MILD SOAP AND WATER. IF IRRITATION DEVELOPS AND PERSISTS, SEEK MEDICAL ATTENTION. DO NOT REUSE CLOTHING/SHOES UNTIL THOROUGHLY LAUNDERED. INHALATION: REMOVE FROM EXPOSURE. IF BREATHING IS DIFFICULT, ADMINISTER OXIGEN. IF BREATHING HAS STOPPED, ADMINISTER ARTIFICIAL RESPIRATION. KEEP PERSON WARM & QUIET. SEEK MEDICAL ATTENTION IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING-TRANSPORT TO HOSPITAL IMMEDIATELY.

---

### SECTION VII – SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SOAK UP SPILL WITH SAND OR OTHER ABSORBENT. PLACE IN CONTAINERS. WASH AREA.

WASTE DISPOSAL METHOD:DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

---

## **SECTION VIII – SPECIAL PROTECTION INFORMATION**

---

RESPIRATORY PROTECTION: USE NIOSH/MSHA APPROVED RESPIRATOR WHEN TLV IS EXCEEDED

VENTILATION: USE WITH ADEQUATE VENTILATION.

PROTECTIVE GLOVES: RUBBER GLOVES SHOULD BE USED.

EYE PROTECTION: SAFETYGLASSES REQUIRED

OTHER PROTECTIVE EQUIPMENT: N/A

---

## **SECTION IX – REGULATORY INFORMATION**

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN COOL PLACE

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS TIGHLY CLOSED.